

# Emkarate® RL 68H

## Typical Properties Data Sheet



### Description

**Emkarate® RL68H** is an ISO VG 68 synthetic polyol ester (POE) lubricant formulated specifically for use in refrigeration and air-conditioning compressors using HFC refrigerants. This product provides effective wear protection for steel and aluminium surfaces for increased system life and improved efficiency and is suitable for both initial fill and service fill. The combination of low temperature characteristics and unparalleled chemical and thermal stability enable the use of **Emkarate® RL68H** over a wide operating temperature range.

Analysis	Method	Typical Value
Viscosity @ 40°C (cSt)	ASTM D445	68.3
Viscosity @ 100°C (cSt)	ASTM D445	9.5
Viscosity Index	ASTM D2270	122
Pour Point (°C)	ASTM D97	-39
Density @ 20°C (g/ml)	ASTM D1298	0.977
Flash Point COC (°C)	ASTM D92	270
Acid Value (mg KOH/g)	ASTM D974	0.02
Colour (Hazen units)	ISO2211	80
Water (ppm)	ASTM D6304	25
Miscibility (Low °C) 10% Lube in R134a	In House	-26
Miscibility (High °C) 10% Lube in R134a	In House	>80
Hydroxyl Value (mg. KOH/g)	ASTM E326	4

\*These values are not intended for use in preparing specifications. Additional technical information is available upon request.

**CPI Fluid Engineering**  
www.cpifluideng.com



**North and South America**  
The Lubrizol Corporation  
2300 James Savage Road  
Midland, MI 48642, USA

Telephone: 1 (989) 496-3780  
Email: sales@cpifluideng.com

**Europe, Middle East and Africa**  
Lubrizol Limited  
Pavilion One, Belasis Court  
Greenwood Road  
Stockton-on-Tees  
TS23 4AZ, UK

Telephone: +44 1642 565266  
Email: euafricamesales@cpifluideng.com

**Asia-Pacific**  
Lubrizol Southeast Asia (Pte) Ltd  
44 Tanjung Penjuru  
Singapore 609032

Telephone: + 65-66638 684  
Email: asiasales@cpifluideng.com

